



LWCD1 TECHNICAL DATA

Dimensions (mm)	LWCD1
Finish (Ext/Int)	Stainless Steel / Stainless Steel
Width (Ext/Int)	880/677
Depth (Ext/Int)	850/522
Height (Ext/Int)	528/268
Drawer Opening	1360
Capacity cu.ft/ltrs	3.3/94
Temperature (°C)	-18/-22°C
Climate Class	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Automatic Hot Gas
Noise level (dBA)	41

Fittings

Drawers	1
---------	---

Electrical / Energy Data - R290 Refrigerant

Refrigerant	R290
Energy Efficiency Class	D
Energy Consumption (kW / 24hrs)	4.41
Start Up (Amps)	7.7
Running (Amps)	1.46
Heat Rejection	305



Key Features

- Large capacity drawer size 2x1 GN (150mm maximum depth)
- Stacking capability for convenient refrigerator/freezer combination
- Removable refrigeration system designed for easy service and maintenance
- Environmentally friendly R290 natural refrigerant has a low GWP/zero ODP
- Foodsafe stainless steel exterior and interior
- Heavy duty, non-marking swivel castors with brakes
- Magnetic balloon door gaskets with 100% tight seal
- CoolSmart controller
- High performance helium leak testing
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential and zero ODP (Ozone Depletion Potential))
- Designed and engineered to operate efficiently up to a 43°C ambient

Options

- Low level castors with brakes
- Adjustable legs in lieu of castors (when suiting with prime cooking stations)*
- Helicoil cable
- GN Pan 2/1 50mm deep
- Heat resistant worktop (increases height by 9mm)
- Stacking kit

IMPORTANT NOTES:

*Alters height by -28mm to +22mm

Energy consumption is tested to EN16825 in 24hrs

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Heat rejection is evaporating at -10°C in 32°C Ambient

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

