



### **EXCEPTIONAL CUT PROTECTION FOR THE FOOD INDUSTRY**

Uncoated, cut resistant glove suitable for food handling. This mediumweight knitted glove has a long cuff to protect the wrist and is ideal for workers in the food industry at risk from cuts due to sharp kitchen equipment.

# Cut resistant: Level E (EN 388:2016) 10gg mediumweight glove for a comfortable wearing experience Long cuff to protect the wrist and forearm Washable at high temperatures Food safe Ambidextrous for easy and quick donning and doffing Individually packed for convenient one glove usage

### **SUITABLE FOR**

### **Typical Industries**

- Food
- Meat

### **Suitable Applications**

- Cutting
- Deboning
- Handling sharp parts
- Sharpening cutting equipment

## EN 388:2016 EN 388:2016 OX43E See overleaf for explanation







## **✓ SKYTEC** MICHIGAN NTT

### **SUITABLE FOR**

MATERIALS	LINER:	HPPE, glass fibre, nylon
	COATING:	N/A
COLOUR	Blue	
LENGTH (mm)	350 (Size Dependent)	
CUFF STYLE	Knitted	


### ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKY00110 SKY00111 SKY00112 SKY00113 SKY00114 SKY00115	1 glove per bag 120 gloves per case

### RECOMMENDATIONS FOR USE

- CLEANING / MAINTENANCE Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. If any damage is found on the gloves they should be disposed of. Gloves should not be left in contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown.
- STORAGE Ideally stored in dry conditions between 10°C and 30°C in the original packaging and sheltered from direct light. Do not exceed 40 °C.
- OBSOLESCENCE When stored as recommended, the gloves will not suffer a change in mechanical properties for up to three years from the date of manufacture. Service life cannot be specified and depends on the application and it is the responsibility of user to ascertain suitability of the glove for its intended use.
- GENERAL None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer. If reaction was to occur, then obtain medical assistance
- CAUTION! Avoid using near moving machinery due to entanglement
- PLEASE NOTE The results of the physical tests should help in glove selection, however it must be understood that actual conditions of use cannot be simulated and it is the responsibility of the end user and not the manufacturer to determine glove suitability for the intended use.

### **CERTIFICATION LEGENDS**





**FOOD CONTACT** DIRECTIVE 2002 / 72 EC

### **ABOUT GLOBUS**

World leader in protecting hands, Globus serves organisations with bespoke hand protection solutions built from a professional range of high performance protective gloves.

Globus is proud to offer bespoke solutions that deliver robust commercial benefits not just safety improvements. We have an enviable track record in helping to reduce hand accident rates whilst delivering improved comfort and productivity as well as waste and cost reductions.

Globus applies its expertise across a spectrum of industries, meeting and exceeding a diverse range of hand protection requirements; from the rigorous demands of the petrochemical and construction industries to the complexities of clean room and aerospace manufacturing.

Find out why leading companies rely on a solution from Globus to help implement a comprehensive hand protection policy. Contact us today.

### **EUROPE**

### www.globus.co.uk

E: sales@globus.co.uk +44 (0)161 877 4747 +44 (0)161 877 4746

### MIDDLE EAST AND AFRICA

### www.globusgroup.com/gcc

E: gcc@globusgroup.com T: +971 4 882 9962 F: +971 4 882 9963

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

© 2019 Globus (Shetland) Ltd | SKY-DATA-MICH NTT-0219 1