



Refrigerated Chef Base

BD20032, BD20036, BD20048

- Designed to accommodate heavy equipment including Opus 800 Series chargrills, griddles and hobs
- Three widths available – 800mm, 900mm and 1200mm
- Drawers hold 1/1 GN 100mm deep container/s
- Allows bulk storage and easy access to food at point of cooking
- Ideal for meat and fish
- Adjustable digital thermostat -2° to +8°
- Self closing heavy duty drawers
- Supplied on castors as standard



Chef Base Features

- Designed to accommodate heavy equipment including Opus 800 Series chargrills, griddles and hobs
- Drawers hold 1/1 GN 100mm deep container/s
- Adjustable digital thermostat -2° to +8°
- Self closing heavy duty drawers on stainless steel rollers
- Gas R452A
- CFC-free refrigeration system has an expansion valve for rapid temperature recovery
- Foamed in place CFC free polyurethane insulation provides highest insulation factor available
- Rubber magnetic door gaskets provide a positive seal

Cleaning and Servicing

- Removable drawers
- Interior corners are rounded for easy cleaning
- Rubber magnetic door gaskets provide easy cleaning
- Available on castors to make it easier to pull unit out for deep cleaning

Overall Construction

- Top, front, sides, back, drawers and interior cavity are 304 grade stainless steel
- Rubber magnetic door gaskets provide a positive seal
- Supplied on castors as standard
- Available on 6" adjustable stainless steel legs
- Gas R452A
- CFC-free refrigeration system has an expansion valve for rapid temperature recovery
- Foamed in place CFC free polyurethane insulation provides highest insulation factor available
- Mullion coils are coated to resist corrosion and provide maximum air flow for even cooking
- 1.8 metre cable with a UK 3 pin plug



Technical Data

	BD20032	BD20036	BD20048
Width (mm)	813	914	1219
Depth (mm)	826	826	826
Height (mm)	660	660	660
Number of drawers	2	2	2
1/1 GN Capacity	2	2	4
Drawer width internal (mm)	457	457	660
Drawer depth internal (mm)	635	635	635
Cooled Volume (cu. m.)	0.11	0.11	0.19
Total power rating (kW)	0.6	0.6	0.6
Electrical supply 1N~+E 230V 50-60Hz Current Rating (Amps)	2.6	2.6	2.6
Net weight full (kg)	147	154	186