



MODEL T29/T29A

SOFT SERVE FREEZER

TWIN TWIST, COUNTERTOP, DIGITAL CONTROL



Ideal for medium capacity outlets to add soft serve ice cream and frozen yogurt. innovative design keeps operation simple and helps reduce cost of ownership.



FAST FREEZE DOWN

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption



DIGITAL CONTROL AND DISPLAY

Digital control provides access to system settings and displays critical system information



LOW MIX INDICATOR

Light turns "ON" at low mix to alert operator to add mix



SELF CLOSING DISPENSING VALVE

Automatically prevents product overflow after dispense



DISPENSE SPEED CONTROL

Provides flexibility in dispense rate control for different applications



HOPPER AGITATORS

Maintain product consistency and prevent product separation



AUTO PROGRAMMING

Allows automatic switching of operation modes based on preset schedules



STANDBY

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight



SAFETY PROTECTIONS

- Low temperature and motor overload shut-off to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating
- Thermal overload to protect from motor overheating

SIMPLE BUT POWERFUL CLASSY DESIGN THAT OFFERS OUALITY AND EASE OF USE


MAXIMISE YOUR PROFITS






MODEL T29/T29A

SOFT SERVE FREEZER MACHINE





















SPECIFICATIONS

WEIGHT

Flavours	2 + Twist
Freezing Cylinders	2 x 1.7L
Mix Hoppers	2 x 12L
Output Capacity (80 grams)	300 serves/hr
Clearance Requirements	152mm/6" on left

Net	155 / 344	165 / 367
Shipping	170/ 378	180 / 400
Volume	0.57 CBM / 19	.97 CBF
DIMENSIONS	NET (MM/IN)	SHIPPING (MM/IN)
DIMENSIONS Width	NET (MM/IN) 552 / 21.7	SHIPPING (MM/IN) 620 / 24.4
	,	, , ,

KG/LB (Gravity)

KG/LB (Pump)

208-230/60/1	16 amps single phase	NA
220-240/50/1	16 amps single phase	NA
ELECTRICAL	AMP	POWER(KW)

FEATURES

CONTROL SYSTEMS	SINGLE DIGITAL
REFRIGERATED HOPPERS	V
HOPPER AGITATOR AVAILABLE	V
TEMPERATURE DISPLAY	V
STANDBY MODE	V
AUTO CLOSING DISPENSING VALVES	V
DISPENSING SPEED CONTROL	✓
LOW MIX INDICATOR LIGHT	√
LOW MIX INDICATOR ALARM	✓
LOW TEMPERATURE PROTECTION	V
MOTOR AMPERAGE PROTECTION	<u> </u>
HIGH PRESSURE PROTECTION	✓
THERMAL OVERLOAD PROTECTION	✓
T29A: AIR PUMP VERSION AVAILABLE	✓

BLUE ICE MACHINES LTD