



# LA135-SA TECHNICAL DATA

Dimensions (mm)	LA135-SA
Finish (Ext/Int)	Stainless Steel / Aluminium
Width (Ext/Int)	606/536
Depth (Ext/Int)	577/434
Height (Ext/Int)	805/606
Door Opening	606
Capacity cu.ft/ltrs	4.8/135
Temperature (°C)	-18/-22°C
Climate Class	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Manual
Noise level (dBA)	44

## Fittings

Shelves	2
Trayslides per door	Fixed

## Electrical / Energy Data

Refrigerant	R290
Energy Efficiency Class	-
Energy Consumption (kW / 24hrs)	-
Start Up (Amps)	7.7
Running (Amps)	1.3
Heat Rejection	300



## Key Features

- Stainless steel exterior with aluminium interior
- Barrel locked doors
- Magnetic balloon door gaskets
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential).
- Front vented refrigeration system
- CoolSmart controller
- Designed and engineered to operate efficiently up to 32°C ambient
- Air cooled condensing unit
- High performance helium leak testing

## Options

- 50mm castors
- Left hand hung door

## IMPORTANT NOTES:

\*Energy consumption is tested to EN16825in 24hrs

\*\*Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration  
Bryggen Road,  
North Lynn Industrial Estate  
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000  
Spares: +44(0) 1553 817 017  
E info@williams-refrigeration.co.uk  
W www.williams-refrigeration.co.uk

