



Authorized Distributor:
FOODSERVICE EQUIPMENT MARKETING
 10 CARRON PLACE-KELVIN IND.ESTATE G75 0YL GLASGOW()
 TEL./FAX. 0044-1355 244111 / 0044-1355 241471
 E-mail:doherthyj@fem.co.uk



Sirman Slicers , model Palladio 300 Aut. Top :

- Rounded design, no sharp edges and visible screws.
- Chrome plated and ground slide rod.
- Lapped cast iron slide rod bushing.
- Vulcanized rubber stops on carriage.
- Removable support cover for thickness gauge plate.
- Stainless steel slice deflector with bayonet fitting.
- Stainless steel screws and fittings.
- Enclosed and sealed belt pulley.
- 49,5 mm distance between blade and motor.
- Bottom cover.
- Power source 220V.
- Built in sharpening tool with bottom protection.
- Standard blade removal tool.
- Ergomic controls – push buttons with IP67 protection rating.
- 3 speed selection
- 3 different adjustments for carriage travel.
- Slice counter.
- Slice number setting with automatic stop feature.
- Enclosed and sealed drive motor.
- Positive drive belt.
- Carriage release system for manual slicing.
- Output slicers per minute: 37 - 70



Controls






Large hopper



More space between blade and body machine

Data sheet



Technical data

Model	PALLADIO 300 TOP AUT.
ø Blade	mm 300 - inch. 12
Motor	watt 275+200 - Hp 0,37+0,27
Cut thickness	mm 23
Run of carriage	mm 310
Hopper	mm 365x270
A	mm 465
B	mm 340
C	mm 615
D	mm 660
E	mm 465
F	mm 730
G	mm 650
L	mm 630
X	mm 240/270
Y	mm 190

Palladio : Palladio 300 Aut. Top

H	mm 240
W	mm 220
Net weight	kg 38
Shipping	mm 870x840x750
Gross weight	kg 53
HS-CODE	84385000