



# TW15 TECHNICAL DATA

| Dimensions (mm)           | TW15                              |
|---------------------------|-----------------------------------|
| Finish (Ext/Int)          | Stainless Steel / Stainless Steel |
| Width (Ext/Int)           | 1510/1217                         |
| Depth (Ext/Int)           | 385/305                           |
| Depth Lid Open            | 447                               |
| Height (Ext/Int)          | 241/105                           |
| Height Lid Open           | 563                               |
| Capacity 1/3GN Containers | 7                                 |
| Temperature (°C)          | +4/+8°C                           |
| Power Supply              | 230V/50Hz/1Ph                     |
| Fuse (Amps)               | 13                                |
| Noise level (dBA)         | 42                                |

## Fittings

|                        |                       |
|------------------------|-----------------------|
| GN Pans (not included) | Can accept 1/3 or 1/6 |
|------------------------|-----------------------|

## Electrical / Energy Data - R134A Refrigerant

|                                 |       |
|---------------------------------|-------|
| Refrigerant                     | R134A |
| Energy Consumption (kW / 24hrs) | 1.53  |
| Start Up (Amps)                 | 8.35  |
| Running (Amps)                  | 1.25  |
| Heat Rejection                  | 267   |



## Key Features

- Foodsafe stainless steel exterior and interior
- Designed to accommodate 7 x 1/3 pans
- Digital thermometer and adjustable thermostat
- Designed and engineered to operate efficiently up to a 32°C ambient
- Hinged lid designed to stay open
- Precision injected, high density polyurethane insulation
- Fitted with rubber feet
- Removable unit cover
- Accepts 100mm deep 1/6GN and 1/3GN pans

## Options

- Wall mounting kit
- Counter mounting kit
- Free standing extended legs (350mm incl. feet)
- Bridging bars
- 1/6 Stainless steel gastronorm pans
- 1/3 Stainless steel gastronorm pans

## IMPORTANT NOTES:

\*Energy consumption is tested to EN153 in 24hrs

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

\*\*Heat rejection is evaporating at -10°C in 32°C Ambient

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration  
Bryggen Road,  
North Lynn Industrial Estate  
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000  
Spares: +44(0) 1553 817 017  
E info@williams-refrigeration.co.uk  
W www.williams-refrigeration.co.uk

