



LJC2-SA-U22 TECHNICAL DATA

Dimensions (mm)	LJC2-SA-U22
Finish (Ext/Int)	Stainless Steel / Aluminium
Width (Ext/Int)	1400/870
Depth (Ext/Int)	700/585
Height (Ext/Int)	857/600
Door Opening	-
Capacity cu.ft/ltrs	13.2/374
Temperature (°C)	-18/-22°C
Climate Class	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Automatic Hot Gas
Noise level (dBA)	61

Fittings	
Shelves	N/A
Trayslides per door	N/A

Electrical / Energy Data	
Refrigerant	R290
Energy Efficiency Class	D
Energy Consumption (kW / 24hrs)	6.5
Start Up (Amps)	14.2
Running (Amps)	2.58
Heat Rejection	623



Key Features

- Foodsafe stainless steel exterior and aluminium interior
- Radiused, easy clean, interior based corners
- Barrel locked drawers
- Magnetic balloon gaskets with 100% tight seal
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential).
- Heavy duty, non-marking swivel castors with brakes
- Removable refrigeration system designed for easy service and maintenance
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- Fully automatic air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing

Options

- Adjustable legs in lieu of castors (add 10mm to height)

IMPORTANT NOTES:

*Energy consumption is tested to EN16825 in 24hrs

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

**Heat rejection is evaporating at -10°C in 32°C Ambient

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

