



Ergo Line

Active Cooling

Ergo Line AC is a light weight, but robust, cart for holding and transportation of cold food with GN1/1 capacity. Detachable U-shaped runners offer safe handling, easy cleaning and optimal temperature distribution. Infinitely variable temperature setting is performed via digital displays which indicates when the selected temperature is reached. Big castors for easy movement. A ScanBox is a Scandinavian designed product made for both back and front of house, especially with the Signature option with the possibility to customize the exterior design. Compressor cooling is offered as an option.

Outer Measurement

| | |
|---------------|---------------|
| Width | 540 mm |
| Height | 1440 mm |
| Depth | 810 / 870* mm |

Inner Measurement

| | |
|---------------|---------------|
| Width | 330 mm |
| Height | 1042 mm |
| Depth | 535 / 545* mm |

Capacity & Weight

| | |
|--|--|
| Capacity | 12 x 1/1GN with 80 mm distance between runners |
| Maximum Loading Capacity / Runner | 9 kg |
| Net Weight | 65 kg |
| Volume | 184 / 187* liter |

Features

| | |
|------------------|---|
| Color | Black (RAL 9005) is standard. Red (RAL 3003) and Grey (RAL 7042). Free of charge. |
| Signature | Put your logo on the box or wrap it in your pattern. |

*Compressor Cooling increases depth to 870 mm

Construction & Electrics

| | |
|--------------------------------|---|
| Interior | Anodized aluminium |
| Rack | Detachable laser cut U-shaped runners in SST |
| Exterior | Fiber glass plastic and aluminum profiles |
| Door Handle | Robust excenter lock. One Grip Handle as an option. |
| Door Opening | 270° with a magnet to keep door at fixed position |
| Top Bumper & Chassi | Stainless Steel. Chassi covered with rubber cladding. |
| Power Connection | 220V-240V / 1 phase / 50-60Hz |

Active Cooling

| | |
|--------------------------------|--------------------|
| Thermoelectric Cooling | Yes |
| Consumption W/A | 340W / 1,48A |
| Temperature Range | +3°C to +10°C |
| DB / ΔT / IP Class / CB | 68 / 23° / 44 / No |

ALTERNATIVE

| | |
|---------------------------|---------------|
| Compressor Cooling | Option |
| Consumption W/A | 135W / 1,05A |
| Temperature Range | +3°C to +10°C |
| DB / ΔT / IP Class | 63 / 30° / 21 |

Functions, Safety & Ergonomics

| | |
|-------------------------------|--|
| Digital Display | Yes, with temperature reached indicator |
| Adjustable Ventilation | No |
| Tray Stop | Protects from door scratches & trays moving |
| Runner Tilt Stop | Extra safety when loading/unloading the box |
| Classifications | CB, CE, EMC, RoHS & REACH |
| Castors (standard) | Ø 160 mm double bearing (2 fixed, 2 swivel w/ brake) |
| Handles | – |
| Extra Loading Spaces | Top bumper keeps extra goods safe on top |

Options

| | | |
|-----------------------------|-------------------------------|--------------------------------|
| Compressor Cooling | Ø 125mm Chromed Castors | Customized Spacing for Runners |
| Central Brake | Ø 160mm CKN Castors | Pressed Runners |
| Card Holders A4/A5/A6 | Ø 200mm Chromed Castors | Stainless Steel Interior |
| One Grip Handle | Ø 200mm Foam Filled Castors | Stainless Steel Exterior |
| One Grip Handle w. Lock Key | Ø 400mm Cross Country Castors | Ergonomic Push/Pull Handles |
| Tow Bars | Ergo Drive+ Motorized Chassi | |

For detailed information of available options please refer to scanbox.se