



Product Code: LR150 13-104

Freezer Undercounter Cabinet



Features & Benefits

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate to ISO Climate class 4 up to 32°C ambient

External Finish

s/s ext Standard

Base Fittings

Castors - Rear Fixed Standard

Levelling Bolts Standard

Electrical, Service & Ecodesign Data

230/50/1 Standard

Fuse Required 13

Internal Finish

aluminium Standard

Doors

Solid Standard

Specification

Dimensions (Width) 605

Dimensions (Height) 830

Dimensions (Depth) 640

Weight (Unpacked, kg) 69

Weight (Packed, kg) 78.1

Gross Volume 150

Noise DbA @ 1M TBC

Shelving

Nylon Coated Shelf Option

Refrigeration

R290 - Energy Efficient Standard

Integral Refrigeration System Standard

Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for airflow, ensure that 25mm clearance is allowed above the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet



Energy



Quality



Value



Design



Hygiene



After Care