



LAZ10CT TECHNICAL DATA

Dimensions (mm)	LAZ10CT
Finish (Ext/Int)	Stainless Steel / Aluminium
Width (Ext/Int)	885/805
Depth (Ext/Int)	734/533
Height (Ext/Int)	870/460
Door Opening	358
Capacity cu.ft/ltrs	8.3/234
Temperature (°C)	-18/-22°C
Climate Class	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Automatic Hot Gas
Noise level (dBA)	61

Fittings

Shelves	4
Trayslides per door	4

Electrical / Energy Data

Refrigerant	R290
Energy Efficiency Class	D
Energy Consumption (kW / 24hrs)	5.94
Start Up (Amps)	14.2
Running (Amps)	2.59
Heat Rejection	623



Key Features

- Foodsafe stainless steel exterior and interior base, with aluminium interior walls
- Integral 'easy grab' door handle
- Self closing doors
- Magnetic balloon door gaskets
- Anti-tilt trayslides
- Removable racking system
- Castors to rear, adjustable feet to front for cabinet stability
- Designed and engineered to operate efficiently up to 43°C ambient
- Precision injected, high density up to 75mm polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- CoolSmart controller
- Front vented refrigeration system for excellent performance
- Fully automatic air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing

Options

- Stainless steel interior
- Additional shelving / trayslides

IMPORTANT NOTES:

*Energy consumption is tested to EN16825in 24hrs

**Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

